

Versatill® T12 Designed Fluid

Description

Versatill® Designed Fluids are based on fluorinated (HFE) and chlorinated (t-DCE) carbons and cover a wide spectrum of applications: from elastomer and plastic cleaning, to cleaning -defluxing of electronic components and assemblies; precision-cleaning of any metal parts, to heavy-duty degreasing of metals, in cold-immersion or through vapor-degreasing. Versatill® Fluids are non-flammable, environmentally sound, user-friendly and economical, making them ideal cost-effective and efficient replacements for ANY non-flammable brominated, chlorinated or fluorinated solvent.

Versatill® T12 is a non-azeotropic formulation, best used in cold-cleaning and aerosol applications, to aggressively clean and degrease metal and ceramic surfaces. It is an excellent replacement for many solvents, including CFCs, PFCs, HFEs, HCFCs (HCFC-141b, HCFC-225) and aqueous cleaners, in terms of performance and cost.

Features

- Ideal for cold-cleaning applications, including immersion, wipes and aerosols
- Outstanding performance; highest solvency in its class and low surface tension
- Designed for cleaning heavy greases, oils, waxes, silicones and non-polar contaminants with high soils loading capacity
- Non-flammable and low in odor and toxicity for an excellent safety profile
- Environmentally Sound – GWP < 23 and ZERO Ozone Depletion Potential
- Replacement for nPB, TCE, ozone-depleting HCFC and other inefficient, harmful HFC
- Faster cycle times, fast drying, lower energy use

Typical Physical Properties

The following technical information and data should be considered representative or typical only and should not be used for specification purposes. Final product specifications are available by request.

Properties	Versatill® T12	Novac™ 71D90	Opteon™ SE79	nPB	TCE	HCFC- 141b	HCFC- 225
Boiling Point (°C/°F)	48 (118)	43 (109)	47 (117)	71 (160)	87(188)	32 (90)	54 (129)
Liquid Density (g/mL)	1.29	N/A	1.29	1.35	1.44	1.24	1.55
Surface Tension (dynes/cm)	20	N/A	21	26	32	32	16
Kauri-Butanol Value	112	N/A	103	125	129	129	31
Vapor Pressure mmHg @ 20°C (68°F)	352	N/A	335	112	N/A	518	216
Viscosity (cP)	0.41	N/A	0.42	0.49	0.54	0.54	0.59
Heat of Vaporization (cal/g @ boiling point)	59.5	N/A	66.9	58.8	56.4	56.4	34.6

Applications

- Cleaner-Degreaser of oil and grease
- Electrical parts (dielectric strength 35K)
- Defluxing printed circuit boards
- Precision cleaning
- Metal cleaning
- Carbon removal
- Silicone stripping
- Drying agent

Environmental Properties and Safety Profile

Properties	Versatill® T12	Novac™ 73DE	Opteon™ SE79	nPB	TCE	HCFC- 141b	HCFC- 225ca/cb
Ozone Depletion Potential (ODP)	0	N/A	0	0.026	0	0.1	0.03
Global Warming Potential (GWP)	3	N/A	15	<1	<1	782	127/525
Flash Point (TCC)	None	N/A	None	None	None	None	None
Flammability Limits (v%)	7-15	N/A	7.2-15.2	4-7.8	8.3-12.5	7.6-17.7	N/A
Exposure Guideline (ppmv)	200	N/A	200	0.1	10	500	50

Material Compatibility

Testing of Versatill® T12 Designed Fluid concluded compatibility of a wide range of metals, plastics and elastomers.

Metal*		Plastics**		Elastomers**	
Compatible	Incompatible	Compatible	Incompatible	Compatible	Incompatible
Aluminum		Acetal	ABS	PTFE	Silicone
Brass		Epoxy	Acrylic	Perfluoroelastomers	Fluorosilicone
Carbon Steel		Nylon	Polycarbonate	Parfluor™	Buna N
Copper		PEEK	Styrene	Viton™ (perfluor)	Viton™ Non-fluor
Inconel		Polyester	PolySulfone	PTFE with EPDM	EPDM
Magnesium		Polyethylene			Butyl rubber
Monel		Polypropylene		PTFE with Neoprene	Neoprene
Stainless Steel		PTFE			
Titanium					

*Metals tested in accordance with Mil-T-81533A, the metal corrosion test

**Plastics and elastomers were tested for changes in weight, dimensions and appearance after immersion in boiling temperatures for minutes followed by an hour drying.

Conformity

Versatill® T12 Designed Fluid conforms to the following specifications:

- **AMS 1562B** Aircraft exterior surfaces (except for ASTM F484 Acrylic Stress Cracking)
- **ARP 1755B** Aircraft engine cleaning
- **ASTM-F-945** Stress Corrosion of titanium alloys (aircraft engine)
- **Boeing D6-17487P** Exterior and general cleaner

Regulations

With its favorable health and environmental properties, t-DCE is subject to less stringent and fewer regulations than other chlorinated solvents.

- Versatill® T12 is not reportable under SARA 313
- Versatill® T12 is not regulated as a hazardous waste under RCRA
- Versatill® T12 is not regulated as a hazardous air pollutant under NESHAP

Packaging & Storage

Versatill® T12 is available in 250 Kg drums (551 lbs) and 23 Kg pails (50 lbs).

This product should be stored in original containers, in a cool, dry and ventilated place. Do not expose to temperatures higher than 120°F

© 2022 Solvents Company, Inc. All rights reserved. The above information is furnished in good faith and believed to be accurate and reliable. Neither representations nor warranties are made, expressed or implied. User should make their own tests and determine suitability of the product to their needs. Nothing in here shall be construed as a permission for a use which might infringe upon a patent. Versatill® is a trademark licensed to Solvents Company, Inc.